

A SECTION SIMILAR TO THIS WOULD BE NEEDED TO GET THE 50% PERVIOUS CREDIT FROM THE CITY OF BROOKHAVEN

For pedestrian applications the pavers and openings may be replaced with 3" to 4" stone

OPENINGS TO BE 3/8" TO 1/4" AND SHALL MAKE UP 10-20% OF TOTAL AREA

TYP. NO. 8 AGGREGATE IN OPENINGS

No. 89, 9, 10 may be used but not finer material

CONCRETE PAVERS MIN. 3 1/8 IN. (80 MM) THICK

CURB/EDGE RESTRAINT WITH CUT-OUTS FOR OVERFLOW DRAINAGE (CURB SHOWN)

CURB OPTIONAL, DEPENDING ON APPLICATION

CITY OF BROOKHAVEN

NO SAND, GRAVEL, OR FINES ALLOWED TO GET 50% PERVIOUS CREDIT

CITY OF BROOKHAVEN

BEDDING COURSE 1 1/2 TO 2 IN. (40 TO 50 MM) THICK (TYP. NO. 8 AGGREGATE)

4 IN. (100 MM) THICK NO. 57 STONE OPEN-GRADED BASE

No. 89, 9, 10 may be used but not finer material

GEOTEXTILE ON SIDE AND TOP OF SUBBASE

MIN. 6 IN. (150 MM) THICK

NO. 2 STONE SUBBASE

No. 3 may also be used


OPTIONAL GEOTEXTILE ON BOTTOM

SOIL SUBGRADE

NOTE: NO CREDIT WILL BE GIVEN FOR PAVERS ON A SLOPE GREATER THAN 5%

NOTES:

1. 2 3/8 IN. (60 MM) THICK PAVERS MAY BE USED IN PEDESTRIAN APPLICATIONS.
2. NO. 2 STONE SUBBASE THICKNESS VARIES WITH DESIGN. CONSULT ICPI PERMEABLE INTERLOCKING CONCRETE PAVEMENT MANUAL.



PERMEABLE PAVEMENT WITH FULL EXFILTRATION TO SOIL SUBGRADE

DRAWING NO.

ICPI-68

SCALE

NO SCALE